

# C10

Tipo : <i>Type :</i>	C10	do: 10mm	
<b>Omologazione</b> <b>Homologation</b>	<b>PN</b>	<b>Coefficiente efflusso ridotto</b> <b>Low flow coefficient</b>	<b>Campo di taratura</b> <b>Setting range</b>
E.D. 2014/68/EU IV Cat.(PED)	16	0,69	0,3 - 16,0 bar
EAC	16	0,69	0,3 - 16,0 bar
ATEX Ex II 2 G c	16	0,69	0,3 - 16,0 bar
ATEX Ex II 2 D c	/	/	/
ASME VIII Div.1	16	0,712	1,0 - 16,0 bar
Canadian Reg. CRN	16	0,712	1,0 - 16,0 bar
<b>CONFIGURAZIONE - CONFIGURATION</b>			
<b>Materiale</b> <b>Material</b>	<b>Ottone</b> <b>Brass</b>	<b>Mista Ottone-Acciaio inox</b> <b>Mixed Brass-Stainless steel</b>	<b>Acciaio inox</b> <b>Stainless steel</b>
<b>Modelli</b> <b>Model</b>	Senza Ghiera <i>Without ring nut</i>	/	Senza Ghiera <i>Without ring nut</i>
	Con anellino <i>With ring</i>	/	Con anellino <i>With ring</i>
	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/
<b>Sedi di Tenuta</b> <b>Seal System</b>	N.B.R. (Std) -10 / + 100 °C	/	N.B.R. (Std) -10 / + 100 °C
	E.P.D.M. -50 / + 150 °C	/	E.P.D.M. -50 / + 150 °C
	VITON -20 / +200 °C	/	VITON -20 / +200 °C
	SILICON -60 / +200 °C	/	SILICON -60 / +200 °C
	TEFLON -196 / +250 °C	/	TEFLON -196 / +250 °C
	KALREZ -20 / +250 °C	/	KALREZ -20 / +275 °C
	/	/	/
<b>Connessione Entrata</b> <b>Inlet Connection</b>	G.3/8" - 1/2" ISO228	/	G.3/8" - 1/2" ISO228
	R.3/8" - 1/2" EN10226	/	R.3/8" - 1/2" EN10226
	3/8" - 1/2" NPT	/	3/8" - 1/2" NPT
	/	/	3/4" Tri Clamp
	/	/	/
	/	/	/
	/	/	/
<b>Connessione Uscita</b> <b>Outlet Connection</b>	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/
	/	/	/

A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPESL),

**TÜV, RINA, Bureau Veritas, ABS e Lloyd**

*On request tests can be made by the most prestigious societies, such as: INAIL (area ISPELS), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.*

**Note:**