

# E10/L150

Tipo : E10/L150

do: 10mm

Type :

**Omologazione  
Homologation**

**PN**

**Coefficiente efflusso  
ridotto  
Low flow coefficient**

**Campo di taratura  
Setting range**

E.D. 2014/68/EU  
IV Cat.(PED)

150

0,86

100,0 - 150,0 bar

EAC

150

0,86

100,0 - 150,0 bar

ATEX Ex II 2 G c

150

0,86

100,0 - 150,0 bar

ATEX Ex II 2 D c

150

0,86

100,0 - 150,0 bar

ASME VIII Div.1

/

/

/

Canadian Reg. CRN

/

/

/

## CONFIGURAZIONE - CONFIGURATION

**Materiale  
Material**

**Ottone  
Brass**

**Mista Ottone-Acciaio  
inox  
Mixed Brass-Stainless  
steel**

**Acciaio inox  
Stainless steel**

**Modelli  
Model**

Con ghiera  
With ring nut  
Senza Ghiera  
Without ring nut

Con ghiera  
With ring nut  
Senza Ghiera  
Without ring nut

Con ghiera  
With ring nut  
Senza Ghiera  
Without ring nut

/

/

/

/

/

/

/

/

/

/

/

/

/

/

/

**Sedi di Tenuta  
Seal System**

N.B.R. (Std) -10 / + 100 °C

N.B.R. (Std) -10 / + 100 °C

N.B.R. (Std) -10 / + 100 °C

E.P.D.M. -50 / + 150 °C

E.P.D.M. -50 / + 150 °C

E.P.D.M. -50 / + 150 °C

VITON -20 / +200 °C

VITON -20 / +200 °C

VITON -20 / +200 °C

SILICON -60 / +200 °C

SILICON -60 / +200 °C

SILICON -60 / +200 °C

TEFLON -196 / +250 °C

TEFLON -196 / +250 °C

TEFLON -196 / +250 °C

KALREZ -20 / +250 °C

KALREZ -20 / +250 °C

KALREZ -20 / +275 °C

/

Metal -196 / +250 °C

Metal -196 / +450 °C

**Connessione Entrata  
Inlet Connection**

G.3/4" - 1" - 1"1/4 ISO228

G.3/4" - 1" - 1"1/4 ISO228

G.3/4" - 1" - 1"1/4 ISO228

R.1/2" - 1" - 1"1/4

R.3/4" - 1" - 1"1/4

R.3/4" - 1" - 1"1/4

EN10226

EN10226

EN10226

1/2" - 1" - 1"1/4 NPT

3/4" - 1" - 1"1/4 NPT

3/4" - 1" - 1"1/4 NPT

DN20-25-32 PN16-160

1" - 1"1/2 Tri Clamp

1" - 1"1/2 Tri Clamp

3/4" - 1" - 1"1/4 150-1500

DN20-25 PN16-160

DN20-25 PN16-160

/

3/4" - 1" 150-1500 lb

3/4" - 1" 150-1500 lb

/

/

/

**Connessione Uscita  
Outlet Connection**

G.1"1/4 ISO228

G.1"1/4 ISO228

G.1"1/4 ISO228

DN32 PN16-160

1"1/2 Tri Clamp

1"1/2 Tri Clamp

1"1/4 150-1500 lb

DN32 PN16-160

DN32 PN16-160

/

1"1/4 150-1500 lb

1"1/4 150-1500 lb

/

/

/

/

/

/

/

/

/

**A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPEL), TÜV, RINA, Bureau Veritas, ABS e Lloy**

*On request tests can be made by the most prestigious societies, such as: INAIL (area ISPELS), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.*

**Note:**