

# G25

Tipo :	G25	do: 25mm	
Type :			
<b>Omologazione</b> <b>Homologation</b>	<b>PN</b>	<b>Coefficiente efflusso ridotto</b> <b>Low flow coefficient</b>	<b>Campo di taratura</b> <b>Setting range</b>
E.D. 2014/68/EU IV Cat.(PED)	60	0,78	0,3 - 60,0 bar
EAC	60	0,78	0,3 - 60,0 bar
ATEX Ex II 2 G c	60	0,78	0,3 - 60,0 bar
ATEX Ex II 2 D c (1)	60	0,78	0,3 - 60,0 bar
ASME VIII Div.1	40	0,629	1,0 - 30,0 bar
Canadian Reg. CRN	40	0,629	1,0 - 30,0 bar
<b>CONFIGURAZIONE - CONFIGURATION</b>			
<b>Materiale</b> <b>Material</b>	<b>Ottone</b> <b>Brass</b>	<b>Mista Ottone-Acciaio inox</b> <b>Mixed Brass-Stainless steel</b>	<b>Acciaio inox</b> <b>Stainless steel</b>
<b>Modelli</b> <b>Model</b>	Con ghiera <i>With ring nut</i> Senza Ghiera <i>Without ring nut</i> Con leva <i>With lever</i> / / / /	Con ghiera <i>With ring nut</i> Senza Ghiera <i>Without ring nut</i> Con leva <i>With lever</i> / / / /	Con ghiera <i>With ring nut</i> Senza Ghiera <i>Without ring nut</i> Con leva <i>With lever</i> Con apertura pneumatica <i>With pneumatic opening</i> Pneumatica con sensore <i>Pneumatic with sensor</i>
<b>Sedi di Tenuta</b> <b>Seal System</b>	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICON -60 / +200 °C TEFLON -196 / +250 °C KALREZ -20 / +250 °C /	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICON -60 / +200 °C TEFLON -196 / +250 °C KALREZ -20 / +250 °C Metal -196 / +250 °C	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICON -60 / +200 °C TEFLON -196 / +250 °C KALREZ -20 / +275 °C Metal -196 / +450 °C
<b>Connessione Entrata</b> <b>Inlet Connection</b>	G.1"1/4 - 1"1/2 ISO228 R.1"1/4 - 1"1/2 EN10226 1"1/4 - 1"1/2 NPT DN32-40 PN16-40-60 1"1/4 - 1"1/2 150-300 lb / /	G.1"1/4 - 1"1/2 ISO228 R.1"1/4 - 1"1/2 EN10226 1"1/4 - 1"1/2 NPT 1"1/2 Tri Clamp DN25-32-40 DIN405-11851 DN32-50 PN16-40-60 1"1/4 - 2" 150-300 lb	G.1"1/4 - 1"1/2 ISO228 R.1"1/4 - 1"1/2 EN10226 1"1/4 - 1"1/2 NPT 1"1/2 Tri Clamp DN25-32-40 DIN405-11851 DN32-50 PN16-40-60 1"1/4 - 2" 150-300 lb
<b>Connessione Uscita</b> <b>Outlet Connection</b>	G.1"1/2 ISO228 DN40-50 PN16-40-60 1"1/2 - 2" 150-300 lb / / / /	G.1"1/2 ISO228 1"1/2 Tri Clamp DN32-40 DIN405-11851 DN40-50 PN16-40-60 1"1/2 - 2" 150-300 lb / /	G.1"1/2 ISO228 1"1/2 Tri Clamp DN32-40 DIN405-11851 DN40-50 PN16-40-60 1"1/2 - 2" 150-300 lb / /

**A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPEL), TÜV, RINA, Bureau Veritas, ABS e Lloyd**

*On request tests can be made by the most prestigious societies, such as: INAIL (area ISPELS), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.*

**Note: (1) No Modello Con leva / No Model With lever**