

E14/L150

Tipo : E14/L150

do: 14mm

Type :

Omologazione Homologation

PN

Coefficiente efflusso ridotto

Low flow coefficient

Campo di taratura Setting range

E.D. 2014/68/EU
IV Cat.(PED)

150

0,86

100,0 - 150,0 bar

EAC

150

0,86

100,0 - 150,0 bar

ATEX Ex II 2 G c

150

0,86

100,0 - 150,0 bar

ATEX Ex II 2 D c

150

0,86

100,0 - 150,0 bar

ASME VIII Div.1

/

/

/

Canadian Reg. CRN

/

/

/

CONFIGURAZIONE - CONFIGURATION

Materiale Material

**Ottone
Brass**

**Mista Ottone-Acciaio
inox
Mixed Brass-Stainless
steel**

**Acciaio inox
Stainless steel**

Modelli Model

Con ghiera
With ring nut
Senza Ghiera
Without ring nut

Con ghiera
With ring nut
Senza Ghiera
Without ring nut

Con ghiera
With ring nut
Senza Ghiera
Without ring nut

/

/

/

/

/

/

/

/

/

/

/

/

/

/

/

Sedi di Tenuta Seal System

N.B.R. (Std) -10 / + 100 °C

N.B.R. (Std) -10 / + 100 °C

N.B.R. (Std) -10 / + 100 °C

E.P.D.M. -50 / + 150 °C

E.P.D.M. -50 / + 150 °C

E.P.D.M. -50 / + 150 °C

VITON -20 / +200 °C

VITON -20 / +200 °C

VITON -20 / +200 °C

SILICON -60 / +200 °C

SILICON -60 / +200 °C

SILICON -60 / +200 °C

TEFLON -196 / +250 °C

TEFLON -196 / +250 °C

TEFLON -196 / +250 °C

KALREZ -20 / +250 °C

KALREZ -20 / +250 °C

KALREZ -20 / +275 °C

/

Metal -196 / +250 °C

Metal -196 / +450 °C

Connessione Entrata Inlet Connection

G.1" - 1"1/4 - 1"1/2

G.1" - 1"1/4 - 1"1/2

G.1" - 1"1/4 - 1"1/2

ISO228

ISO228

ISO228

R.1" - 1"1/4 - 1"1/2

R.1" - 1"1/4 - 1" 1/2

R.1" - 1"1/4 - 1" 1/2

1" - 1"1/4 - 1"1/2 NPT

1" - 1"1/4 - 1" 1/2 NPT

1" - 1"1/4 - 1" 1/2 NPT

DN25-32-40 PN16-160

1" - 1"1/2 Tri Clamp

1" - 1"1/2 Tri Clamp

1" - 1"1/4 - 1"1/2 150-

DN25-40 DIN405-11851

DN25-40 DIN405-11851

/

DN25-32 PN16-160

DN25-32 PN16-160

/

1" - 1"1/4 150-1500 lb

1" - 1"1/4 150-1500 lb

Connessione Uscita Outlet Connection

G.1"1/2 ISO228

G.1"1/2 ISO228

G.1"1/2 ISO228

DN40 PN16-160

1"1/2 - 2" Tri Clamp

1"1/2 - 2" Tri Clamp

1"1/2 150-1500 lb

DN40 DIN405-11851

DN40 DIN405-11851

/

DN40 PN16-160

DN40 PN16-160

/

1"1/2 150-1500 lb

1"1/2 150-1500 lb

/

/

/

/

/

/

A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPEL), TÜV, RINA, Bureau Veritas, ABS e Lloy

On request tests can be made by the most prestigious societies, such as: INAIL (area ISPELS), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.

Note: