

G15

Tipo :	G15	do: 15mm	
Type :			
Omologazione Homologation	PN	Coefficiente efflusso ridotto Low flow coefficient	Campo di taratura Setting range
E.D. 2014/68/EU IV Cat.(PED)	25	0,69	0,3 - 16,0 bar
EAC	25	0,69	0,3 - 16,0 bar
ATEX Ex II 2 G c	25	0,69	0,3 - 16,0 bar
ATEX Ex II 2 D c (1)	25	0,69	0,3 - 16,0 bar
ASME VIII Div.1	/	/	/
Canadian Reg. CRN	/	/	/
CONFIGURAZIONE - CONFIGURATION			
Materiale Material	Ottone Brass	Mista Ottone-Acciaio inox Mixed Brass-Stainless steel	Acciaio inox Stainless steel
Modelli Model	Con ghiera <i>With ring nut</i> Senza Ghiera <i>Without ring nut</i> Con leva <i>With lever</i> / / / /	Con ghiera <i>With ring nut</i> Senza Ghiera <i>Without ring nut</i> Con leva <i>With lever</i> / / / /	Con ghiera <i>With ring nut</i> Senza Ghiera <i>Without ring nut</i> Con leva <i>With lever</i> Con apertura pneumatica <i>With pneumatic opening</i> Pneumatica con sensore <i>Pneumatic with sensor</i>
Sedi di Tenuta Seal System	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICON -60 / +200 °C TEFLON -196 / +250 °C KALREZ -20 / +250 °C /	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICON -60 / +200 °C TEFLON -196 / +250 °C KALREZ -20 / +250 °C Metal -196 / +250 °C	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICON -60 / +200 °C TEFLON -196 / +250 °C KALREZ -20 / +275 °C Metal -196 / +450 °C
Connessione Entrata Inlet Connection	G.1/2" - 3/4" - 1" ISO228 R.1/2" - 3/4" - 1" EN10226 1/2" - 3/4" - 1" NPT DN20-25 PN16-40 3/4" - 1" 150-300 lb / /	G.1/2" - 3/4" - 1" ISO228 R.1/2" - 3/4" - 1" EN10226 1/2" - 3/4" - 1" NPT 1" - 1"1/2 Tri Clamp DN25 DIN405-11851 DN20-25 PN16-40 3/4" - 1" 150-300 lb	G.1/2" - 3/4" - 1" ISO228 R.1/2" - 3/4" - 1" EN10226 1/2" - 3/4" - 1" NPT 1" - 1"1/2 Tri Clamp DN25 DIN405-11851 DN20-25 PN16-40 3/4" - 1" 150-300 lb
Connessione Uscita Outlet Connection	G.1" ISO228 DN25 PN16-40 1" 150-300 lb / / / /	G.1" ISO228 1"1/2 Tri Clamp DN25 DIN405-11851 DN25 PN16-40 1" 150-300 lb / / /	G.1" ISO228 1"1/2 Tri Clamp DN25 DIN405-11851 DN25 PN16-40 1" 150-300 lb / / /

A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: **INAIL (area ISPESL)**,

TÜV, RINA, Bureau Veritas, ABS e Lloyd

On request tests can be made by the most prestigious societies, such as: INAIL (area ISPELS), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.

Note: (1) No Modello Con leva / No Model With lever